

# DK50 2V/50/M

## Four dental units

**DK50 2V/50**  
without soundproofing box ■

**DK50 2V/50S**  
with soundproofing box ■

**DK50 2V/50/M**  
without box, with n-psl dryer ■

**DK50 2V/50S/M**  
with soundproofing box, with n-psl dryer ■



| Technical specification                            | DK50 2V/50/M | DK50 2V/50S/M |
|--|--------------|---------------|
| Nominal voltage (V/Hz)                             | 230/ 50      |               |
| Maximal current of compressor (A)                  | 8            | 8.2           |
| Compressor efficiency (l.min <sup>-1</sup> /5 bar) | 115*         |               |
| Air tank capacity (l)                              | 50           |               |
| Pressure range (bar)                               | 6 - 8        |               |
| Mode of operation of compressor                    | S1 - 100%    |               |
| Noise level (dB[A])                                | ≤ 71         | ≤ 56          |
| Weight (kg)  | 66           | 118           |
| Dimensions (w x l x h) (mm)                        | 595x585x770  | 750x715x1015  |

\* Part of the efficiency of compressor is used for regeneration of the dryer.  
Technical modifications are subject to change.



Absolute Air and Gas Ltd.  
Unit 6, Isidore Road  
Bromsgrove Technology Park  
Bromsgrove, B60 3FJ

Phone: +44 845 605 6660  
Fax: +44 1527 559262  
enquiries@absoluteairandgas.co.uk  
www.absoluteairandgas.co.uk